

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**


**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>H04M</b>		<b>A2</b>	(11) International Publication Number: <b>WO 97/01913</b>
			(43) International Publication Date: 16 January 1997 (16.01.97)
(21) International Application Number: PCT/GB96/01502 (22) International Filing Date: 21 June 1996 (21.06.96) (30) Priority Data: 9513138.9          28 June 1995 (28.06.95)          GB (71) Applicant (for all designated States except US): GPT LIMITED [GB/GB]; New Century Park, P.O. Box 53, Coventry CV3 1HJ (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): ARNOLD, John, Spencer [GB/GB]; 32 Manor Park, Nether Heyford, Northants NN7 3NN (GB). (74) Agent: BRANFIELD, Henry, Anthony; GEC Patent Dept., Waterhouse Lane, Chelmsford, Essex CM1 2QX (GB).		(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>Without international search report and to be republished upon receipt of that report.</i>	

(54) Title: CONGESTION AVOIDANCE



(57) Abstract

A switched Asynchronous Transfer Mode network has three buffers at the input of the network which hold ATM cells for Constant Bit-Rate traffic, Sustainable Cell-Rate traffic and Available Bit-Rate traffic respectively, the latter two buffers having a lower controlled rate of cell egress than the first of the buffers, the rates of egress being controlled in response to the relationship of the contents of the buffers to upper and lower specified values.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

CONGESTION AVOIDANCE

The existing Public Switched Telephone Network (PSTN) carries voice services over constant-bit-rate channels which are committed for the duration of a call; therefore congestion  
5 may only occur at call set-up.

The existing Packet Switched Public Data Network (PSPDN) carries data in packets over virtual-channels which are statistically-multiplexed onto bearers. Congestion may occur at any time but the integrity of the data is protected by the integral High Level Data Control (HDLC)  
10 protocol which operates link-by-link.

The PSTN is inefficient in carrying data because the channel occupies bandwidth whether or not it carries information.

15 The PSPDN is not able to carry a voice dialogue because of the delay-variation introduced by statistical-multiplexing and the integral HDLC protocol.

An Asynchronous Transfer Mode (ATM) network is required to carry a mixture of the two traffic types described above; its traffic characteristics and features are therefore  
20 fundamentally different from either the PSTN or the PSPDN. The present invention is to identify and provide solutions for the handling of the different traffic classes in the access layer of an ATM infrastructure.

According to the present invention there is provided a switched Asynchronous Transfer

Mode (ATM) network comprising a plurality of switches and having at or adjacent to the input of the network a set of three first-in first-out (FIFO) buffers for receiving calls comprising ATM traffic, the buffers being for Constant Bit-Rate (CBR) traffic, Sustainable Cell-Rate (SCR) traffic and Available Bit-Rate (ABR) traffic forms of ATM traffic respectively, the output rates from the SCR and ABR buffers being controlled by increasing the output rate of a buffer by a small increment when the contents of the buffer exceed an upper specified value and reducing the output rate by a small increment when the contents of the buffer are less than a lower specified value.

10 The present invention will now be described by way of example, with reference to the accompanying drawings, in which:-

Figure 1 shows a block diagram illustrating an ATM Access Upstream Buffer for use in the present invention;

15 Figure 2 shows a block diagram illustrating Traffic Shaping and Congestion Avoidance as carried out in the present invention; and

Figure 3 shows a block diagram illustrating the ATM Flow-Control Loop of the present invention.

20 The International Telecommunications Union (ITU) Study Group 13 recognises three ATM traffic classes; these are:-

\* Constant Bit-Rate (CBR) (class A)

Principally to carry voice.

- \* Sustainable Cell-Rate (SCR) (class B)  
Principally to carry variable bit-rate video.
- \* Available Bit-Rate (ABR) (class Y)  
Used to carry data.

5

One of these traffic classes is associated with each virtual-channel at set-up time.

The SCR and ABR traffic-classes together are defined as bursty; that is, the instantaneous bandwidth occupied by a virtual-channel (VC) is continuously varying.

10

The mean bandwidth of a bursty VC is substantially lower than the peak bandwidth. An ATM switch will provide a multiplexing function at its output ports including a memory buffer which allows the multiple sources to queue for access to the bearer, thus smoothing the traffic flow. When many bursty channels are carried in one bearer the probability of coincidence of peaks resulting in overflow of the finite memory of the buffer queue is relatively low. Thus, it is possible to dimension the network based on virtual-channel bandwidths approaching the mean and hence carry many more channels than would have been the case if dimensioning was based on peak bandwidth; known as the "statistical-gain" of the system.

15

20

The quality-of-service provided, in terms of cell-loss probability, is dependent upon the maximum permitted peak channel bandwidth (the lower the channel bandwidth the larger the number of channels carried and hence the lower the standard-deviation from the statistical mean for the bearer), the size of the memory buffer in the switch (the larger the buffer the longer the period of burst integration) and the "burstiness" of the traffic flow entering the switch.

Limiting the VC peak bandwidth is a function of the system control and VC policing functions provided and switch memory-buffers need to be relatively small both to minimise cost and avoid excessive delay. Bursty traffic can, however, be "conditioned" in the access network in order to achieve a smoother traffic flow before entering the switching network. A large memory buffer positioned adjacent to the point of entry to the access network. All bursty traffic (SCR and ABR classes) is directed via this buffer. However, SCR traffic - more sensitive to delay and delay-variation than ABR traffic - is given the higher priority for egress from the buffer.

CCR traffic is already "smooth" and voice quality will suffer from delay thus this traffic class will use a separate and smaller buffer with priority over the bursty buffer with priority over the bursty buffer for access upstream.

The resultant structure of the upstream buffers is illustrated in Figure 1; however, simple buffering is not enough on its own to smooth the traffic flow. If the output rate is significantly greater than the mean input rate, then the queue in the buffer will be nearly empty and the output will retain much of the burstiness of the input. The output must therefore be rate-controlled so as to create a traffic flow which comes close to emulating that of a CCR channel. However, if the output rate is too restricted then the buffer will fill up and may overflow; thus, a feedback mechanism is required which constrains the output flow sufficiently to maintain a fairly constant level in the buffer.

The size of the bursty traffic buffer is maintained between limits by the mechanisms shown in Figure 2. If the queue size falls below the lower limit then the output rate from the

buffer is incrementally reduced; similarly, if the size goes above the upper limit the output rate is increased. With small increments of change the output rate will change relatively slowly, hence creating a smooth flow of cells.

5 ITU recommendations provide for a 3-bit cell-type field in the header of each ATM cell and one of the codes in this field is for a congested indication. This indication is set by any switch or statistical-multiplexer in the path of a VC or Virtual Path (VP) when there are signs of the approach of congestion; usually when the buffer contents exceed a pre-set value. The intention is that persistence of the congested indication, detected at the destination User-Network  
10 Interface (UNI) (above or below the 'T' reference point depending upon implementation), will result in the return to the source of a congested-message.

The cell-type field also provides for identifying a resource-management (RM) cell which is transmitted over the return path of the related Virtual-Channel and carries the congested-  
15 message. In fact, RM cells are returned at regular intervals (e.g. every N cells received on the channel) whether or not a persistence of congested-indications has been detected.

An RM Cell received at the source may indicate one of three conditions of the upstream track which result in the following actions:

20

1. Congested: shifts the buffer limits (together) one increment up the buffer until the upper buffer margin is reached.  
  
Extends the period over which the bursty input is integrated.  
  
Temporarily reduces the output rate of the buffer (until it refills).



6

Increases the path delay.

2. Hold: maintains the present state.
- 5 3. Uncongested: shifts the buffer limits (together) one increment down the buffer until the lower buffer margin is reached.  
Eventually restores the original state.

10

CLAIMS

1. A switched Asynchronous Transfer Mode (ATM) network comprising a plurality of switches and having at or adjacent to the input of the network a set of three first-in first-out  
5 (FIFO) buffers for receiving calls comprising ATM traffic, the buffers being for Constant Bit-Rate (CBR) traffic, Sustainable Cell-Rate (SCR) traffic and Available Bit-Rate (ABR) traffic forms of ATM traffic respectively, the output rates from the SCR and ABR buffers being controlled by increasing the output rate of a buffer by a small increment when the contents of the buffer exceed an upper specified value and reducing the output rate by a small increment  
10 when the contents of the buffer are less than a lower specified value.
2. A network as claimed in Claim 1, wherein cells in the CBR buffer have a first priority for egress, cells in the SCR buffer have a second priority for egress and cells in the ABR buffer have the lowest priority for egress.  
15
3. A network as claimed in Claim 1 or 2, wherein each cell has in a header thereof a field which may be set by a switch to indicate the onset of a congested condition in the buffers and at the addressed destinations of the network Resource Management (RM) cells are periodically transmitted to the input, the RM cell carrying in the payload thereof information indicating when  
20 persistent receipt of cells carrying the indication of a congested condition is occurring and the receipt of RM cells at the input and carrying such information causing the lower and upper specified values to be moved jointly up the buffer until a limiting upper value is reached.
4. A network as claimed in Claim 3 wherein subsequent receipt of RM cells at the input not

carrying such information causing the lower and upper specified values to be lowered jointly in the buffer until a limiting lower value is reached.





Fig.3.

